

H05V2-R (LYc)

H05V2-R

Cable manufactured according to the harmonized standard (H), for rated voltage 300/500V (05), with insulation made of heat-resistant PVC (V2) and with multi wire conductor (-R)

Application

Single-conductor general purpose power cable designed for use in fixed installations inside equipment or devices and inside luminaires of rated voltage not exceeding 300/500V. Cable insulation made of heat-resistant thermoplastic PVC with maximum working temperature +90°C.

Technical data

Conductor: Cu-ETP1 (acc. to EN 13602), multi wire, class 2 (acc. to EN 60228)
Insulation: PVC, type TI3 (acc. to EN 50363-3)
Sheath: Not applicable
Temperature range: Up to +90°C
Standard: EN 50525-2-31
 Cables conform to the requirements of REACH Regulation and RoHS Directive.

Technical characteristics
H05V2-R (LYc)

Number of conductors x Nominal Cross-section mm ²	Conductor structure		Resistance at 20°C mΩ/m	Insulation thickness mm	Sheath thickness mm	Outer diameter of cable		Approximate weight of cable kg/km
	Number of wires	Single wire diameter				(min.)	(max.)	
		(max.) mm				mm	mm	
1 x 0,50	7	--	36,0	0,6	--	2,0	2,4	9,2
1 x 0,75	7	--	24,5	0,6	--	2,2	2,6	11,9
1 x 1,00	7	--	18,1	0,6	--	2,3	2,8	14,9

Contact

Tel: +48 12 631 10 70

E-mail: biuro@manex.com.pl